

FORCE 165 PLASTIC CARRY CASE



WITH MASK
CARRY CASE
ACCESSORIES



- Direct current (DC) MMA electrode inverter welding machine, 150A. Supplied with welding accessories and plastic carry case.
- Usable electrodes: rutile, basic, stainless steel, cast iron, etc. up to 4 mm.-----
- Advanced arc control devices: arc force, hot start, anti-stick. -----
- Thermostatic, overvoltage, undervoltage, overcurrent protection. Compatible for use with the motor generator (230V, +/- 15%).
- High stability of the welding current in power supply voltage variations.
- Light and compact. Easy to transport. Contained consumption thanks to inverter technology.

DESCRIPTION

MMA inverter, electrode welding machine in direct current (DC).

Usable electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Reduced weight and dimensions
- High welding current stability in spite of mains voltage fluctuations
- Arc force, hot start and anti-stick devices
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator ($\pm 15\%$) protections.

Complete with MMA welding accessories and plastic carry case.



TECHNICAL DATA

CODE	CODE 815857	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	F	MAINS FREQUENCY 50 / 60 Hz
A_{MIN} / A_{MAX} / DC	CURRENT RANGE IN DC 10 - 150 A	TELWIN % USE 20°C	%USE (20°C USE) (*) 60% @ 150A	A_{MAX} / 40°C / DC	MAX CURRENT DC EN60974-1 140 @ 7% A
V₀ DC	MAX NO LOAD VOLTAGE IN DC 72 V	A_{MAX}	MAX ABSORBED CURRENT 31 A	P_{MAX}	MAX ABSORBED POWER 4,1 kW
P_{MIN} / GEN	MOTORGENER. MINIMUM POWER 6 kW	η	EFFICIENCY 82 %	ϕ	POWER FACTOR(cosphi) (cosphi) 0,6
\emptyset / MIN / MAX / DC	D.USABLE ELECTRODES IN DC 1,6 - 4 mm	IP	PROTECTION DEGREE IP21	LxWxH	DIMENSIONS (LxWxH) 38 x 42 x 17 cm
kg	WEIGHT 5,5 kg	% USE	(*)%USE: Dato ideato da TELWIN,	% USE	(*)%USE: non presente nella EN 60974-1

SUPPLIED ACCESSORIES



PLASTIC CARRY CASE
322800



CABLE 16 MMQ 1,8 M - PLUG ATLAS 25
124508



TOLEDO 250 WORK CLAMP 250A
712030



SLAG REMOVER
712139



DALLAS 300 ELECTRODE HOLDER 300A
712260

ON REQUEST ACCESSORIES



RUTILE ELECTRODES D. 2 MM 15
PCS
802617



RUTILE ELECTRODES D. 2,5 MM
15 PCS
802618



RUTILE ELECTRODES D. 3,2 MM
10 PCS
802619



RUTILE ELECTRODES D. 4 MM 8
PCS
802620



STAINLESS STEEL ELECTRODES D.
3,2 MM 8 PCS
802624



RUTILE ELECTRODES D. 2 MM 2,5
KG
802737



RUTILE ELECTRODES D. 2,5 MM
2,5 KG
802739



RUTILE ELECTRODES D. 3,2 MM 4
KG
802749

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



BROCHURE



CERTIFICATE

ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

ГРАФИК РАБОТЫ:

Пн. – Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00

Вс.: с 10:00 по 16:00

КОНТАКТЫ:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара: <https://storgom.ua/product/svarochnyi-invertor-telwin-force-165.html>

Другие товары: <https://storgom.ua/inventory.html>